





How do I delete a functional location?

Delete Functional location

1. The delete flag should be set for the functional location.
2. Run program RIARCTPV via SE38 transaction and enter in the functional location.
3. Then execute program RIARCTPA via SE38 transaction, which will create a file.
4. Execute program RIARCTPD, and select the session from above step 2, after executing which will delete the functional location.



How do I delete a functional location?



Program Edit Goto System Help

Functional Location Archiving Preparation Program

Functional location X-TY to

Functional location category to

Structure indicator to

Test mode

Detail log



Log Edit Goto System Help

Log Display

```
Program RIARCTPV started: 2009.09.11 14:45:43
Client : 402
Function : X-TY
Function cat. :
Structure indicator :
Testmode :

Function X-TY is being edited
-> no other usage found, status DEFL/DEIN possible
-> System status DEFL, set/possible
Statistics:
-> according to sel. condition read 1
-> Data records with deletion flag 1
-> System status DEFL, set/possible 1
Program RIARCTPV ended: 2009.09.11 14:45:46
```

Program Edit Goto Utilities(M) Environment System Help

ABAP Editor: Initial Screen

Debugging With Variant Variants

Program RIARCTPA Create

Subobjects

- Source Code
- Variants
- Attributes
- Documentation
- Text elements

Display Change

How do I delete a functional location?



Program Edit Goto System Help

Functional Location Archiving: Generate Archive File

Functional location: X-TY to

FuncLocCategory: to

Structure indicator: to

Control Data

Test mode

Generate archive file

Detail log

Comment



Program Edit Goto System Help

Functional Location Archiving: Generate Archive File

Functional location: X-TY to

FuncLocCategory: to

Structure indicator: to

Control Data

Test mode

Generate archive file

Detail log

Comment



Log Display

```
Program R1ARETPA started: 2008.09.11 14:49:38
Client: 400
FuncLoc: X-TY
FuncLoc cat:
StrIndicator:
Test mode:
Generate archive data: X
Altern. label:

FuncLoc: X-TY is being edited
Stat1Stat10:
-> according to se1, condition read: 1
Program R1ARETPA ended: 2008.09.11 14:49:40
```



How do I delete a functional location?


Functional Location Archiving: Generate Archive File

Functional Location Archiving: Generate Archive File 1



Summary

Archiving Session Number	000037
Number of Written Data Objects	1
Size of Archiving Session in MB	0.016
Proportion of Header Data in %	90.0
Occupied Database Space in MB	0.004
- Tables	0.002
- Indexes	0.001



Type	No.
ADARCH_KT1	1
Key Table for Archiving Class (Type	
ADARCH_RT1	1
Reference Table for Archiving Class	
CDHDR	1
Change document header	
CDKEYTAB	1
Archiving class CHANGEDOCU transfer	
CDPOS	3
Change document items	
IFLOT	1
Functional Location (Table)	
IFLOTX	1
Functional Location: Short Texts	
ILOA	1
PM Object Location and Account Assig	
JCDS	8



How do I delete a functional location?



How do I delete a functional location?



How do I delete a functional location?

Resource Guide

Recommended Reading

mySAP Certification - Criteria For Application

The guidelines: Criteria to applying for a SAP Certification:

<http://www.erpgreat.com/general/mysap-certification.htm>

Tcodes used for SAP Plant Maintenance

Transaction codes used in plant maintenance.

<http://www.erpgreat.com/plant/tcodes-used-for-sap-plant-maintenance.htm>

SAP PM Support Problem Solution

Problem and Solution in plant maintenance.

<http://www.erpgreat.com/plant/sap-pm-support-problem-solution.htm>

SAP PM Questions Answers on Functional Locations

Questions and Answers on functional location for PM.

<http://www.erpgreat.com/plant/sap-pm-questions-answers-on-functional-locations.htm>

PM Orders and Change Documents

How to activate the document changes log for PM?

<http://www.erpgreat.com/plant/pm-orders-and-change-documents.htm>